



### STREET NAME SIGN MATERIAL SPECIFICATIONS:

1. ALUMINUM BLANKS  
6" X 18", 24", 30", 36" X .08"
2. MARKINGS SHALL BE PLACED ON ONE SIDE OF SIGN ONLY.
3. TEXT SIZE SPECIFICATION:
  - 3.1. 4" INITIAL UPPERCASE.
  - 3.2. 3" NOMINAL LOOP LOWERCASE – NOT INCLUDING ASCENDING AND/OR DESCENDING TAIL.
  - 3.3. 2" BLOCK NUMBER.
  - 3.4. 2" ROUTE DESIGNATION – ALL CAPS – CENTER WITH BLOCK NUMBER.
4. TWO SIGNS SHALL BE MOUNTED BACK TO BACK ON EITHER SIDE OF THE SIGN POST. 2 SIGNS ARE REQUIRED.
5. GREEN BACKGROUND WITH WHITE TEXT FOR PUBLIC STREETS.
6. WHITE BACKGROUND WITH GREEN TEXT FOR PRIVATE STREETS.
7. PROVIDE 'T2000 HWYC' FONT.

### STREET NAME SIGN MATERIAL AND SPACING SPECIFICATIONS:

1. ALL STREET NAME SIGNS SHALL COMPLY WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD), MOST CURRENT VERSION, REVISION AND/OR SUPPLEMENT, FOR SIGN MATERIAL(S), SIZE, THICKNESS, SHAPE, COLOR(S), MESSAGE, SYMBOLOGY AND RETROREFLECTIVITY.
2. FINAL STREET NAME SIGN LOCATION AND/OR PLACEMENT SHALL BE IN ACCORDANCE WITH THE MUTCD AND AS DETERMINED AND APPROVED BY THE CITY ENGINEER OR SIGN SHOP SUPERVISOR.
3. SPACING BETWEEN EACH SIGN ON A SINGLE POLE SHALL BE NO GREATER THAN 1" AND MUST NOT OVERLAP.
4. ALL OTHER SIGNS SHALL DEFAULT TO MUTCD STANDARDS AND SPECIFICATIONS.



Engineering Division

#### Typical Street Name Sign Standard

Approved By  
City Engineer  
Kevin J. Slovarp

Adopted: 03/15/2006  
Revised: 01/13/2017

**STD - 721**